


“FOUNDATION” – MODERATE COMMERCIAL SOLUTION DYED POLYPROPYLENE TILE

Product definition		Tufted loop pile
Gauge		1/10"
Pile fibre		100% solution dyed Polypropylene
Pile weight	ISO 8543	385gr/m ² ± 7.5%
Pile height	ISO 1766	3.0mm ± 5%
Tile backing		Bitumen with a fibreglass scrim
Total thickness	ISO 1765	6.0mm ± 5%
Total weight	ISO 8543	4150gr/m ² ± 7.5%
Tile size		500mm × 500mm
Tiles per box		20 = 5m ²
Use classification	Method EN 1307	Class 31 Moderate Commercial
Abrasion resistance	ISO 12951	Pass
Thermal isolation	ISO 8302	0.10 m ² K/W
Dimensional stability	EN 986	Pass
Sound absorption	ISO 140-8	20dB (26 dB with Acoustic Backing)
Static loading		Anti-static
Reaction to fire	EN 13501-1	Cfl-s1
Light fastness	ISO 105 B02	5.0
Rubbing, wet	ISO 105×12	3.0
Wear warranty		5 Year Moderate Commercial

MONOLITHIC QUARTER TURN



TILES: 500 × 500mm
PLANKS: 250 × 1000mm (available by Special Order only)



26dB WHEN ORDERED WITH ACOUSTIC BACKING (20dB is standard rating)

GENERAL

Planks and Acoustic Backing	Both are available on Special Order only – please ask for more details
Suitability	Moderate Commercial Use areas: office, retail, hospitality, leisure and educational
Recommended Maintenance	Please refer to CCTUK installation and maintenance guidelines for details of suitability.
Preparation	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards. Areas larger than 30m ² – it is advised that a suitable tackifier be used.
Dye Lots	Colours may vary from batch to batch, it is therefore advised when ordering a large continuous area, tiles of the same batch are specified when ordering.
Pile Direction	Best results are obtained when using the illustrated laying patterns.
Warranties	All warranties are subject to CCTUK T&C (available on request).